

	Small Difference	Medium Difference	Large Difference
Small Delta rate of change	Zero weight (0.0)	Small weight (0.2)	Medium weight (0.7)
Medium Delta rate of change	Zero weight (0.0)	Medium weight (0.7)	Large weight (1.0)
Large Delta rate of change	Small weight (0.2)	Large weight (1.0)	Large weight (1.0)
—110		<u>Figure 2</u>	
DETERMINI	E FIRST	122	106
PARAMETER VALUE GENERATED			
BY CONTROL SYSTEM		— MEASURE	MAP/BAROMETRIC
		124	PRESSURE
INDEPENDENTLY GENERATE		ESTIMATE	
A SECOND VALUE FOR THE —		→ MODEL, OR ├─	ENGINE SPEED
FIRST PARAI	METER	CALCULATE	
			MASS AIRFLOW
DETERMINE A DI	FFERENCE —	RATIO	L
BETWEEN THE FIRST AND			—142
SECOND VALUES		PERCENT 144	
<u> </u>			
DETERMINE A RATE OF			
CHANGE OF THE DIFFERENCE			
BETWEEN THE VALUES			
.			
DETERMINE AND APPLY A		<u>Figure 4</u>	
WEIGHTING FACTOR BASED ON			
THE DIFFERENCE AND/OR RATE OF CHANGE			
RATE OF CH			
STORE WEIGHTED			
IN HISTORY			
V			
STATISTICALLY	PROCESS	INTEGRATED U	SING 182
WEIGHTED DIF	FERENCES	MOVING WIND	
	100		
		SELECT ALTERNATIVE	
CONTROL ENGINE BASED ON		CONTROL STRATEGY WHEN192	
WEIGHTED DIFFERENCES		DIFFERENCE EXCEEDS	
		THRESHOLD	









